



AGRALE MARRUÁ AM41 - VTNE 2½ Ton



BODY	
Cab	Simples - 3 lugares
Dump	Metallic 14 seats
ENGINE	
Make/Model	MWM ACTEON 4.12
Level of Emissions	PROCONVE P5 / EURO III
Emissions Control	Common Rail Electronic Injection
No. of Cylinders	4 in line
Displacement	4.748 cm³
Power	165 cv (121 kw) - 2200 RPM
Torque	600 Nm / 1.200 - 1.600 RPM
Fuel	Diesel
ELECTRIC SYSTEM	
Voltage	24 V
Batteries	2 x 12V / 100 Ah
Alternator	28 V/80 A
CLUTCH	
Type	Organic - Dry single disc
Disc's Outer Diameter	362 mm
Actuation	Air assisted hydraulically operated
DRIVING TRANSMISSION	
Make/Model	EATON FSO 4505 C
No. of Gears	5 Forward /1 Reverse
Reduction Ratio	1ª 5,78:1 / 2ª 2,73:1 / 3ª 1,63:1 / 4ª 1,00: 1 / 5ª 0,770:1 / Reverse 5,26:1
TRANSFER CASE	
Model	Fabco TC-28A Manual / Double Speed (Reduced) Push Button on Dashboard
Ration	2,22 : 1 / 1 : 1
CHASSI	
Type	Ladder Chassis - LNE 38
Length/Width	6.610 x 865 mm
SUSPENSION	
Front	Satellite Dish Springs and Stabilizer Bar
Rear	Semi-Elliptic Springs and Stabilizer Bar
Front/Rear Shock Absorbers	Double-Acting Telescopic
TRACTION AXLE	
Front	Fabco FSD-10A
Type - Front	Traction and directional floating axle
Rear	Meritor MS-19145
Type - Rear	Eixo rígido em aço estampado

THEORETICAL PERFORMANCE (BASED ON NS AND OPC RELATIONS)	
Maximum Speed	96 km/h
Maximum Controlled Speed	4 km/h
Autonomy	600 km
Climb on Ramp in TGW	70%
Ignition on Ramp in TGW (Start Ability)	60%
STEERING WHEEL	
Model	ZF SERVOCOM 8095
Type	Hydraulic
Turning Circle (guide to guide)	11 m
WHEELSETS	
Model	7,5 x 22,5"
TIRES	
Model	275/80 R22,5"
BRAKES	
Service Brake - Type	Drum/ "S CAM" Pneumatic with Automatic Regulation
Actuation	Pneumatic Valve Treadle
Parking Brake - Type	Spring brake 24"
Actuation	Park Brake Valve/Rear Brake
SUPPLY CAPACITY	
Fuel Tank	150 L
Crankcase	8 L c/ filtro
Gearbox	4,6 L
Rear Differential – Volume	6,6 L
Front axle	6,15 L
Cooling liquid	16,5 L
DIMENSIONS	
Distance between axles	3.750 mm
Overall length	7.250 mm
Width (Outer tires) - Front Axle	2.160 mm
Width (Outer tires) - Rear axle	2.355 mm
Width between pants (cab)	2.150 mm
Width Mirror to Mirror	2.840 mm
Car's maximum height	3.270 mm
Minimum height from soil - Front Axle	330 mm
Minimum height from soil - Rear Axle	250 mm
Front gauge	1.880 mm
Approach Angle without Bull Bar	37º
Departure Angle	30º
Maximum ramp	60%
Maximum Side Inclination	30%
Wading depth without snorkel	1000 mm
Maximum degree	350 mm
Turning Circle (wall to wall)	11,2 m

WEIGHTS AND CAPACITIES	
TGW - Total Gross Weight	9.500 kg
MTC - Maximum Traction Capacity	15.500 kg
Kerb weight	7.000 kg
Load Capacity	2500 kg + Towing 2.500 kg (Cargo+Towing)
FEATURES AND OPTIONAL	
SAPA Set	NS
Acelerador Manual	NS
12 Poles Socket	NS
Heating System	OPC
Air Conditioner	OPC
Headrest	NS
Fog Lights	NS
Lights Protectors	NS
Running Boards	NS
Electric Wich	OPC
Dumpster canvas kit	NS
20L Gallon	NS (2 units)
Matte Green Color	NS
Bull Bar	NS
Inclinometer	OPC
GPS	OPC

NS (Normal Series) / OPC (Option) / NA (Non-Applicable) Marruá Militar



DEALER

www.agrale.com.br
BR - 116 Km 145, nº 15104
95059-520 - Caxias do Sul - RS
Phone: +55 (54) 3238.8000

This literature is for the product information and illustration only, and Agrale, or the Bidder, are able to offer its products with characteristics or different optional informed here in, valid for both, as final document for the offer, the Commercial Proposed celebrated by the legal representative of the company.

