



TRUCK 10000 S



ENGINE	
Brand/Model	MWM MAXXFORCE 4.8 / CUMMINS ISF 3.8
Level of Emissions	PROCONVE P7 / EURO V
Emissions Control	Pós-Tratamento de gases por Redução Catalítica Seletiva (SCR)
No. of Cylinders/Displacement	4 cil 4748 cm³ / 4 cil 3760 cm³
Maximum Power	165cv(121,32 kw) a 2200rpm / 162cv(119 kw) a 2600rpm
Maximum Torque	600 Nm a 1200 a 1600 rpm / 600 Nm a 1300 a 1700 rpm
Electronic Injection System	COMMON RAIL
Fuel	Diesel
ELECTRICAL SYSTEM	
Tension	24 V
Battery	12 V/100 Ah (02 unidades)
Alternator	28V-80A / 28V-150 Ah
TRANSMISSION	
Clutch	Orgânica - Monodisco a seco c/ acionamento hidráulico
Clutch External Diameter	362 mm (MWM) - 330 mm (Cummins)
Gearbox	EATON FSO 4505 C
No. of Gears	5 a frente/1 a ré
Reductions	1ª 5,78:1 / 2ª 2,73:1 / 3ª 1,63:1 / 4ª 1,00: 1 / 5ª 0,770:1 / ré 5,26:1
AXLE	
Front axle	MERITOR MFS 08
Front	Viga I em aço forjado
Rear axle	MERITOR 15-124 / DANA S16 - 130
Rear	Eixo rígido em aço estampado / Carcaça fundida
Standard ratio (NS)	4,30
Optional reduction ratio (OPC)	3,73* / 3,91 / 4,10 / 4,56 :1 (*) Somente para Dana S16-130
THEORETICAL PERFORMANCE (BASED ON NS AND OPC RELATIONS)	
Maximum Speed	MWM(NS) 102 Km/h Cummins(NS) 115 Km/h MWM(opc) 117 Km/h*, 112 Km/h, 107 Km/h, 96 Km/h Cummins(opc) 130 Km/h*, 127 Km/h, 121 Km/h, 109 Km/h (*) Somente para Dana S16-130
Gradeability (GVW)	MWM(NS) 35,2% Cummins(NS) 35,3% MWM(opc) 29,8 Km/h*, 31,5 Km/h, 33,3 Km/h, 37,8 Km/h Cummins(opc) 29,9 Km/h*, 31,5 Km/h, 33,3 Km/h, 37,8 Km/h (*) Somente para Dana S16-130
Startability (GVW)	MWM(NS) 24,5% Cummins(NS) 24,5% MWM(opc) 21,1%*, 22,2%, 23,3%, 26,1% Cummins(opc) 19,3%*, 20,2%, 23,3%, 26,1% (*) Somente para Dana S16-130
TIRES	
Dimensions	235/75R17,5"
WHEELS	
Dimensions	6.75" x 17,5"
CHASSI	
Type	Escada em LNE 38 - Perfil "C" Parafusado
Front Suspension	Molas parabólicas progressivas e Barra estabilizadora
Rear Suspension	Molas semi-elípticas de duplo estágio e Barra estabilizadora
Front/Rear Shock Absorbers	Telescópicos de dupla ação

BRAKES	
Service Brake	Tambor/ "S CAM" Pneumático Assistido Eletronicamente (ABS/EBD/ATC) com regulagem automática
Engine Brake	Eletro-pneumático/Tubo de escape
Parking Brakes	Spring brake 24"
STEERING	
Model	ZF SERVOCOM 8090
Type	Hidráulica
SUPPLY CAPACITY	
Fuel Tank (Diesel S50)	150 L
Urea Tank (Arla 32)	16 L
Crankcase	9,3 L com filtro / 10,6 L com filtro
Gearbox	4,6 litros
Differential	9,0 / 7,5 L
DIMENSIONS	
Wheelbase	3.750mm / 4350mm
Overall length of chassis for applications	4.335mm / 5.144mm
Overall length	6.560mm / 7.420mm
Width (Mirrors)	2.900 mm
Width (Outer tires) - Front Axle	2.200 mm
Width (Outer tires) - Rear axle	2.224 mm
Turning Circle	15,5 m / 17,0 m
WEIGHTS AND CAPACITIES	
Curb weight	3.650 / 3.675 kg
GVW - Gross Vehicle Weight	10.000 kg
GVW with 3rd axle (installed by others)	12.000 Kg
Payload	6.260/6.200 Kg
MTC - Maximum Traction Capacity	15.500 kg
GCWR - Gross Combined Weight Rating	15.500 kg
Maximum Load of Front Axle	3.200 Kg
Maximum Load of Rear Axle	6.800 Kg
FEATURES AND OPTIONAL	
Engine Brake	NS
Automatic Brake Adjuster	NS
Rear Stabilizer Bar	NS
Clutch servo pneumatic cylinder	NS
Headrest	NS
24V/12V Converter	NS
Air deflectors (front columns)	NS
On-Board Computer in the cluster	NS
Cruise Control	NS
Adjustable steering wheel	Posição Fixa
Taillights	Lâmpadas convencionais
Forced ventilation and defroster	NS
Retractable belts	NS (exceto posição central)
Digital tacograph	NS
Calibration and Cleaning Kit	OPC

FEATURES AND OPTIONAL	
Kit - Sleeper berth	OPC
Kit Hydraulic Tilt Cab	OPC
Heating System	OPC
Kit - Radial Tire Michelin	OPC
Color - Bumper/fender flare/step plate	Preto graneado
Air Conditioner	OPC
Electric Window	OPC
Electric Rearview	OPC
Blind spot mirror (front and right)	OPC
Wide angle (two sides)	OPC
Solid Colors (Yellow, Green, Blue)	OPC
Metallic Colors (Silver, Gray, Brown)	OPC
Urea tank cap with key	NS
Roof hatch	Fixo
Key objects of doors	Apenas lado do motorista
DRL - Daytime Running Light	OPC
Storage box (dashboard)	OPC
Net storage (rear panel)	OPC
Catch-hands ceiling	OPC
Catch-hands doors	OPC
Port-soap	OPC



www.agrale.com.br
BR - 116 Km 145, nº 15104
95059-520 - Caxias do Sul - RS
Phone: +55 (54) 3238.8000

This literature is for the product information and illustration only, and Agrale, or the Bidder, are able to offer its products with characteristics or different optional informed here in, valid for both, as final document for the offer, the Commercial Proposed celebrated by the legal representative of the company.